



INTEGRATED SYSTEMS

- Quick Ferment (TM)
- Fermentation Program (TM)
- Temperature Logs for Food Safety Programs
- Microprocessor IoT Board with WiFi connectivity
- iOS and Android App for remote control
- 7" IPS Touch Screen Display
- LED Interior Light
- Exterior: Stainless Steel
- Interior: Stainless Steel
- Legs: Rolling wheels
- Digital Temperature and Humidity Sensor

388 liter capacity



FERMENTATION MADE EASY



COOLING 1-15°C HEATING 15-65°C

PRODUCT SPECIFICATION

Model number:	HBP2101A
Power supply	1 Phase 220-240V 50hz
Electricity rating:	220V AC 50/60Hz
Power Cord	2.3m
Heater power:	2000W
Cooling power:	300W
Inner dimensions:	540x540x1300mm
Outer dimensions:	700x650x1720mm
Gross weight:	45kg
Heating temp range:	15-65°
Cooling temp range:	1-15°
Humidity sensing:	0-100%
Compressor	Hermetic
Condenser	Fin and Tube type
Refridgerator coolant:	R134a
Electric Circuit Protection:	Earth Wire
Shelf:	540x540 (5pcs)
Shelf clips:	20 pcs
Drainage:	Sealable drain pipe
Operating temperature	10-35°C
Installation clearance:	20mm space for installation